

ARBO

ARBO BOND BREAKER TAPE

Arbo Bond Breaker Tape is a laminated polyethylene cloth tape combined with a pressure sensitive adhesive backing. The laminated polyethylene prevents sealant adhesion to ensure that the sealant does not form a three sided adhesive bond. High bond strength of the pressure sensitive adhesive ensures good adhesion to a variety of common construction substrates. Bond Breaker Tape has good conformability ensuring good adhesion to both regular and irregular surfaces.

MAIN APPLICATIONS

Recommended for sealant joints to ensure that the sealant adheres to the two principle surfaces of the joint only. Bond breaker tape prevents adhesion to the back of the joint. Three sided adhesion can lead to sealant splitting, cracking and early joint failure.

Application

All surfaces to be bonded must be clean and dry.

SHELF LIFE

Not applicable if product is stored in a cool, dry place out of direct sunlight.

HEALTH AND SAFETY

No hazards associated with the product.

PACKAGING

50m x 4.5mm

50m x 20mm

50m x 6mm

50m x 10mm

50m x 12mm

TECHNICAL DATA

Colours	Black
Thickness:	0.2 mm
Application Temperature:	+ 5° C to + 40° C 30
Service Temperature:	50° C to + 150° C
Tensile Strength:	110 – 115 N/25mm

IMPORTANT: The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.



CARLISLE® Adshead Ratcliffe & Co. Ltd United Kingdom

Derby Road | Belper
Derbyshire

DE56 1WJ
United Kingdom

T +44 (0)1773 826661
F +44 (0)1773 821215

E info.arbo@ccm-europe.com
www.arbo.co.uk